

Safety data sheet according to UK REACH

Printing date 21.01.2026

Version number 1

Revision: 21.01.2026

1 Identification of the substance/mixture and of the company/undertaking

· **Product identifier**

· **Trade name:** Opalescence™ Boost (mixed)

· **Article number:**

SDS 199-001.19R01, 1008067, 14094, 14241, 15316, 6247-US, 6248-US, 6249-US, 34567, 13431

· **Relevant identified uses of the substance or mixture and uses advised against**
Professional tooth bleaching gel in-office.

· **Application of the substance / the mixture** Professional tooth bleaching gel in-office.

· **Details of the supplier of the safety data sheet**

· **Manufacturer/Supplier:**

Ultradent Products Inc.
505 W. Ultradent Drive (10200 S)
South Jordan, UT 84095-3942
USA
onlineordersupport@ultradent.com
(800) 552-5512

EC Responsible Person
Ultradent Products GmbH
Am Westhover Berg 30
51149 Cologne Germany
Email: infoDE@ultradent.com
Office Phone: +49(0)2203-35-92-0

· **Further information obtainable from:** Customer Service

· **Emergency telephone number:**

CHEMTREC (NORTH AMERICA) : +1 (800) 424-9300
(INTERNATIONAL) : +(703) 527-3887

2 Hazards identification

· **Classification of the substance or mixture**

· **Classification according to Regulation (EC) No 1272/2008**



GHS03 flame over circle

Ox. Liq. 2 H272 May intensify fire; oxidiser.



GHS05 corrosion

Skin Corr. 1B H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.



GHS07

Acute Tox. 4 H302 Harmful if swallowed.

(Contd. on page 2)

Safety data sheet

according to UK REACH

Printing date 21.01.2026

Version number 1

Revision: 21.01.2026

Trade name: Opalescence™ Boost (mixed)

(Contd. of page 1)

- **Label elements**
- **Labelling according to Regulation (EC) No 1272/2008** Void
- **Hazard pictograms** GHS03, GHS05, GHS07
- **Signal word** Danger
- **Hazard-determining components of labelling:**
Hydrogen Peroxide
Potassium Hydroxide
Sodium Fluoride
- **Hazard statements**
H272 May intensify fire; oxidiser.
H302 Harmful if swallowed.
H314 Causes severe skin burns and eye damage.
- **Precautionary statements**
P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P103 Read carefully and follow all instructions.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 Immediately call a POISON CENTER/doctor.
P321 Specific treatment (see on this label).
P405 Store locked up.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

3 Composition/information on ingredients

- **Mixtures**
- **Description:** Mixture of substances listed below with nonhazardous additions.

- **Dangerous components:**

CAS: 7722-84-1 EINECS: 231-765-0	Hydrogen Peroxide ⚠ Ox. Liq. 1, H271; ⚠ Skin Corr. 1A, H314; ⚠ Acute Tox. 4, H302; Acute Tox. 4, H332 Specific concentration limits: Ox. Liq. 1; H271: $C \geq 70\%$ Ox. Liq. 2; H272: $50\% \leq C < 70\%$ Skin Corr. 1A; H314: $C \geq 70\%$ Skin Corr. 1B; H314: $50\% \leq C < 70\%$ Skin Irrit. 2; H315: $35\% \leq C < 50\%$ Eye Dam. 1; H318: $C \geq 8\%$ Eye Irrit. 2; H319: $5\% \leq C < 8\%$ STOT SE 3; H335: $C \geq 35\%$	>36-<50%
	Synthetic Amorphous, Pyrogenic Silica substance with a Community workplace exposure limit	>1-<10%
CAS: 56-81-5 EINECS: 200-289-5	Glycerin substance with a Community workplace exposure limit	>5-<20%

(Contd. on page 3)

Safety data sheet according to UK REACH

Printing date 21.01.2026

Version number 1

Revision: 21.01.2026

Trade name: Opalescence™ Boost (mixed)

		(Contd. of page 2)
CAS: 7757-79-1 EINECS: 231-818-8	Potassium Nitrate ⚠ Ox. Sol. 2, H272; ⚠ Skin Irrit. 2, H315; STOT SE 3, H335-H336	>1-<10%
CAS: 1310-58-3 EINECS: 215-181-3	Potassium Hydroxide ⚠ Skin Corr. 1A, H314; ⚠ Acute Tox. 4, H302 Specific concentration limits: Skin Corr. 1A; H314: $C \geq 5\%$ Skin Corr. 1B; H314: $2\% \leq C < 5\%$ Skin Irrit. 2; H315: $0.5\% \leq C < 2\%$ Eye Irrit. 2; H319: $0.5\% \leq C < 2\%$	>1-<10%
CAS: 7681-49-4 EINECS: 231-667-8	Sodium Fluoride ⚠ Acute Tox. 3, H301; Acute Tox. 2, H310; ⚠ Skin Irrit. 2, H315; Eye Irrit. 2, H319, EUH032	>0.88-<1.320%

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

4 First aid measures

· **Description of first aid measures**

· **General information:**

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· **After inhalation:**

Seek medical treatment in case of complaints.

In case of unconsciousness place patient stably in side position for transportation.

· **After skin contact:**

If skin irritation continues, consult a doctor.

Immediately wash with water and soap and rinse thoroughly.

· **After eye contact:**

Seek immediate medical advice.

Rinse opened eye for several minutes under running water. Then consult a doctor.

· **After swallowing:**

Call for a doctor immediately.

Drink plenty of water and provide fresh air. Call for a doctor immediately.

· **Most important symptoms and effects, both acute and delayed** No further relevant information available.

· **Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

5 Firefighting measures

· **Extinguishing media**

· **Suitable extinguishing agents:** Water spray

· **Special hazards arising from the substance or mixture**

In closed unventilated containers, risk of rupture due to the increased pressure from decomposition. Contact with combustible material may cause fire.

During heating or in case of fire poisonous gases are produced.

· **Advice for firefighters:**

Use water spray to cool fire exposed surfaces and protect personnel. Move containers from fire area if there isn't any risk.

· **Protective equipment:**

Wear fully protective suit.

(Contd. on page 4)

Safety data sheet according to UK REACH

Printing date 21.01.2026

Version number 1

Revision: 21.01.2026

Trade name: Opalescence™ Boost (mixed)

(Contd. of page 3)

Mouth respiratory protective device.

6 Accidental release measures

· **Personal precautions, protective equipment and emergency procedures**

Keep people at a distance and stay on the windward side.

Keep away from ignition sources.

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

· **Environmental precautions:**

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

· **Methods and material for containment and cleaning up:**

Hydrogen Peroxide may be decomposed by adding sodium metabisulfite or sodium sulfite after diluting to about 5%.

Stop the flow of material, if this is without risk.

Combustible materials exposed to hydrogen peroxide should be immediately submerged in or rinsed with large amounts of water to ensure that all hydrogen peroxide is removed. Residual hydrogen peroxide that is allowed to dry (upon evaporation hydrogen peroxide can concentrate) on organic materials such as paper, fabrics, cotton, leather, wood or other combustibles can cause the material to ignite and result in fire.

Dilute with plenty of water.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Use neutralising agent.

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

· **Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

· **Precautions for safe handling:**

Safety glasses should be used by the patient and doctor. Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166 (EN).

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· **Information about fire - and explosion protection:**

Combustible materials exposed to hydrogen peroxide should be immediately submerged in or rinsed with large amounts of water to ensure that all hydrogen peroxide is removed. Residual hydrogen peroxide that is allowed to dry (upon evaporation hydrogen peroxide can concentrate) on organic materials such as paper, fabrics, cotton, leather, wood or other combustibles can cause the material to ignite and result in fire.

Keep respiratory protective device available.

· **Conditions for safe storage, including any incompatibilities**

· **Storage:**

· **Requirements to be met by storerooms and receptacles:**

Suitable material for receptacles and pipes: Stainless steel.

Suitable material for receptacles and pipes: glass.

Suitable material for receptacles and pipes: Aluminium.

Store only in the original receptacle.

Provide ventilation for receptacles.

(Contd. on page 5)

Safety data sheet according to UK REACH

Printing date 21.01.2026

Version number 1

Revision: 21.01.2026

Trade name: Opalescence™ Boost (mixed)

(Contd. of page 4)

· **Information about storage in one common storage facility:**

- Store away from reducing agents.
- Store away from combustible materials.
- Store away from metals.
- Do not store together with acids.

· **Further information about storage conditions:**

- Store receptacle in a well ventilated area.
- Store in a cool place.
- See product labelling.
- Keep container tightly sealed.

· **Specific end use(s)** Professional dental in-office Tooth Bleaching Gel

8 Exposure controls/personal protection

· **Control parameters**

· **Ingredients with limit values that require monitoring at the workplace:**

7722-84-1 Hydrogen Peroxide

<i>WEL</i>	Short-term value: 2.8 mg/m ³ , 2 ppm
	Long-term value: 1.4 mg/m ³ , 1 ppm

Synthetic Amorphous, Pyrogenic Silica

<i>TWA</i>	Short-term value: 6 mg/m ³
------------	---------------------------------------

56-81-5 Glycerin

<i>WEL</i>	Long-term value: 10 mg/m ³
------------	---------------------------------------

1310-58-3 Potassium Hydroxide

<i>WEL</i>	Short-term value: 2 mg/m ³
------------	---------------------------------------

· **Additional information:** The lists valid during the making were used as basis.

· **Exposure controls**

- **Appropriate engineering controls** No further data; see section 7.
- **Individual protection measures, such as personal protective equipment**
- **General protective and hygienic measures:**

- Do not eat or drink while working.
- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing.
- Wash hands before breaks and at the end of work.
- Avoid contact with the eyes.
- Avoid contact with the eyes and skin.

· **Respiratory protection:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· **Hand protection**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

(Contd. on page 6)

Safety data sheet according to UK REACH

Printing date 21.01.2026

Version number 1

Revision: 21.01.2026

Trade name: Opalescence™ Boost (mixed)

(Contd. of page 5)

· **Material of gloves**

The selection of suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact breakthrough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye/face protection**

Use chemical splash goggles and face shield (ANSI Z87.1 or approved equivalent)



Tightly sealed goggles

· **Body protection: Protective work clothing**

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· Physical state	Liquid
· Colour:	Red
· Odour:	Odourless
· Odour threshold:	Not determined.
· Melting point/freezing point:	Undetermined.
· Boiling point or initial boiling point and boiling range	100 °C
· Flammability	Not applicable.
· Lower and upper explosion limit	
· Lower:	Not determined.
· Upper:	Not determined.
· Flash point:	>65 °C
· Decomposition temperature:	Not determined.
· pH at 20 °C	6-8.5
· Viscosity:	
· Kinematic viscosity	Not determined.
· Dynamic:	Not determined.
· Solubility	
· water:	Fully miscible.
· Partition coefficient n-octanol/water (log value)	Not determined.
· Vapour pressure:	Not determined.
· Density and/or relative density	
· Density at 20 °C:	1.2-1.4 g/cm ³
· Relative density	Not determined.
· Vapour density	Not determined.

· **Other information**

· **Appearance:**

· **Form:** Gel

· **Important information on protection of health and environment, and on safety.**

· **Ignition temperature:**

Product is not selfigniting.

· **Explosive properties:**

Product does not present an explosion hazard.

(Contd. on page 7)

Safety data sheet according to UK REACH

Printing date 21.01.2026

Version number 1

Revision: 21.01.2026

Trade name: Opalescence™ Boost (mixed)

(Contd. of page 6)

· Change in condition	
· Evaporation rate	Not determined.
· Information with regard to physical hazard classes	
· Explosives	Void
· Flammable gases	Void
· Aerosols	Void
· Oxidising gases	Void
· Gases under pressure	Void
· Flammable liquids	Void
· Flammable solids	Void
· Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void
· Self-heating substances and mixtures	Void
· Substances and mixtures, which emit flammable gases in contact with water	Void
· Oxidising liquids	May intensify fire; oxidiser.
· Oxidising solids	Void
· Organic peroxides	Void
· Corrosive to metals	Void
· Desensitised explosives	Void

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability** Stable under recommended conditions.
- **Thermal decomposition / conditions to be avoided:** Decomposes when exposed to heat
- **Possibility of hazardous reactions:**
Contact with metals, metallic ions, alkalis, reducing agents and organic matter (such as alcohols or terpenes) may produce self-accelerated thermal decomposition.
Reacts with various metals.
Reacts with organic substances.
- **Conditions to avoid:**
pH Variations
UV rays
Contamination
- **Incompatible materials:**
Heavy Metals
Reducing Agents
Combustible Materials
Alkalis
Organic materials
- **Hazardous decomposition products:** Oxygen

11 Toxicological information

- **Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Harmful if swallowed.

(Contd. on page 8)

Safety data sheet according to UK REACH

Printing date 21.01.2026

Version number 1

Revision: 21.01.2026

Trade name: Opalescence™ Boost (mixed)

(Contd. of page 7)

· **LD/LC50 values relevant for classification:****ATE (Acute Toxicity Estimates)**

Oral	LD50	917 mg/kg
Dermal	LD50	15,837 mg/kg
Inhalative	LC50/4 h	27.8 mg/l

7722-84-1 Hydrogen Peroxide

Oral	LC50 Fish	16.4 mg/l (Fish)
------	-----------	------------------

Synthetic Amorphous, Pyrogenic Silica

Oral	LD50	>5,000 mg/kg (rat) (Oral Test Method)
	LC50 Fish	>10,000 mg/l (Fish) (Toxicity to fish)
Dermal	LD50	>2,000 mg/kg (rabbit) (Dermal test method)
	LC50(Daphnia magna)	>1,000-10,000 mg/l (daphnia) (Toxicity to aquatic invertebrates)

56-81-5 Glycerin

Oral	LD50	7,750 mg/kg (guinea pig)
		4,100 mg/kg (mouse)
		5,570 mg/kg (rat)
		27,000 mg/kg (rabbit)
		>5,000 mg/l (Fish)
Dermal	LC50 Fish	>5,000 mg/l (Fish)
		LD50

7757-79-1 Potassium Nitrate

Oral	LD50	3,015 mg/kg (rat)
		1,901 mg/kg (rabbit)
Dermal	LC50 Fish	1,378 mg/l (Fish)
	LD50	>5,000 mg/kg (rat)
	LC50(Daphnia magna)	490 mg/l (daphnia)

1310-58-3 Potassium Hydroxide

Oral	LD50	214 mg/kg (rat)
	LC50 Fish	80 mg/l (Fish)

7681-49-4 Sodium Fluoride

Oral	LD50	52 mg/kg (mouse)
	LC50 Fish (static)	17 mg/l (Fish)
Dermal	LD50	175 mg/kg (rat)

· **Primary irritant effect:**· **Skin corrosion/irritation** Causes severe skin burns and eye damage.· **Serious eye damage/irritation** Causes serious eye damage.· **Information on other hazards**· **Endocrine disrupting properties**

7681-49-4	Sodium Fluoride	List II
-----------	-----------------	---------

GB

(Contd. on page 9)

Safety data sheet according to UK REACH

Printing date 21.01.2026

Version number 1

Revision: 21.01.2026

Trade name: Opalescence™ Boost (mixed)

(Contd. of page 8)

12 Ecological information

- **Toxicity**

- **Aquatic toxicity:**

7722-84-1 Hydrogen Peroxide

EC50	1.38 mg/l (Algae) 2.4 mg/l (daphnia)
------	---

56-81-5 Glycerin

EC50	>10,000 mg/kg (Bacteria)
------	--------------------------

7681-49-4 Sodium Fluoride

EC50	272 mg/kg (Algae) 98 mg/kg (daphnia)
Algae Toxicity (static)	7 mg/l (Algae)

- **Persistence and degradability** No further relevant information available.
- **Bioaccumulative potential** May be accumulated in organism
- **Mobility in soil** No further relevant information available.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Endocrine disrupting properties** For information on endocrine disrupting properties see section 11.
- **Other adverse effects**
- **Additional ecological information:**
- **General notes:**
Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
Must not reach sewage water or drainage ditch undiluted or unneutralised.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation**
Dispose of contents/container in accordance with international, federal, state, and local regulations.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.
- **Recommended cleansing agents:** Water, if necessary together with cleansing agents.

14 Transport information

- **UN number or ID number**
- **ADR, IMDG, IATA** UN3093
- **UN proper shipping name**
- **ADR** 3093 CORROSIVE LIQUID, OXIDIZING, N.O.S. (HYDROGEN PEROXIDE, AQUEOUS SOLUTION, STABILIZED, POTASSIUM HYDROXIDE)
- **IMDG, IATA** CORROSIVE LIQUID, OXIDIZING, N.O.S. (HYDROGEN PEROXIDE, STABILIZED, POTASSIUM HYDROXIDE)

(Contd. on page 10)

GB

Safety data sheet

according to UK REACH

Printing date 21.01.2026

Version number 1

Revision: 21.01.2026

Trade name: Opalescence™ Boost (mixed)

(Contd. of page 9)

· **Transport hazard class(es)**· **ADR**· **Class**

8 Corrosive substances.

· **Label**

8+5.1

· **IMDG**· **Class**

8 Corrosive substances.

· **Label**

8/5.1

· **IATA**· **Class**

8 Corrosive substances.

· **Label**

8 (5.1)

· **Packing group**· **ADR, IMDG, IATA**

II

· **Environmental hazards:**

Not applicable.

· **Special precautions for user**

Warning: Corrosive substances.

· **Hazard identification number (Kemler code):**

85

· **EMS Number:**

F-A,S-Q

· **Stowage Category**

E

· **Maritime transport in bulk according to IMO instruments**

Not applicable.

· **Transport/Additional information:**· **ADR**· **Limited quantities (LQ)**

1L

· **Excepted quantities (EQ)**

Code: E2

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 500 ml

· **Transport category**

2

· **Tunnel restriction code**

E

· **IMDG**· **Limited quantities (LQ)**

1L

· **Excepted quantities (EQ)**

Code: E2

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 500 ml

(Contd. on page 11)

Safety data sheet according to UK REACH

Printing date 21.01.2026

Version number 1

Revision: 21.01.2026

Trade name: **Opalescence™ Boost (mixed)**

(Contd. of page 10)

· **UN "Model Regulation":** UN 3093 CORROSIVE LIQUID, OXIDIZING, N.O.S. (HYDROGEN PEROXIDE, AQUEOUS SOLUTION, STABILIZED, POTASSIUM HYDROXIDE), 8 (5.1), II

15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

· **Poisons Act**

· **Regulated explosives precursors**

7722-84-1	Hydrogen Peroxide	12%
-----------	-------------------	-----

· **Regulated poisons**

None of the ingredients is listed.

· **Reportable explosives precursors**

7757-79-1	Potassium Nitrate	Listed
-----------	-------------------	--------

· **Reportable poisons**

1310-58-3	Potassium Hydroxide	17% of total caustic alkalinity
7681-49-4	Sodium Fluoride	Listed

· **Directive 2012/18/EU**

· **Named dangerous substances - ANNEX I** None of the ingredients is listed.

· **Seveso category P8** OXIDISING LIQUIDS AND SOLIDS

· **Qualifying quantity (tonnes) for the application of lower-tier requirements** 50 t

· **Qualifying quantity (tonnes) for the application of upper-tier requirements** 200 t

· **Chemical safety assessment:**

Product contains high levels of hydrogen peroxide, which has a known toxicological profile. Product is only to be used by licensed dental professionals using the specified engineering controls.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases from Section 3**

H271 May cause fire or explosion; strong oxidiser.

H272 May intensify fire; oxidiser.

H301 Toxic if swallowed.

H302 Harmful if swallowed.

H310 Fatal in contact with skin.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

EUH032 Contact with acids liberates very toxic gas.

· **Department issuing SDS:** Environmental, Health, and Safety

(Contd. on page 12)

Safety data sheet according to UK REACH

Printing date 21.01.2026

Version number 1

Revision: 21.01.2026

Trade name: Opalescence™ Boost (mixed)

(Contd. of page 11)

· **Contact:** Customer Service

· **Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

ATE: Acute toxicity estimate values

Ox. Liq. 1: Oxidizing liquids – Category 1

Ox. Liq. 2: Oxidizing liquids – Category 2

Ox. Sol. 2: Oxidizing solids – Category 2

Acute Tox. 3: Acute toxicity – Category 3

Acute Tox. 4: Acute toxicity – Category 4

Acute Tox. 2: Acute toxicity – Category 2

Skin Corr. 1A: Skin corrosion/irritation – Category 1A

Skin Corr. 1B: Skin corrosion/irritation – Category 1B

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

· *** Data compared to the previous version altered.**