

Printing date 19.10.2020 Revision: 18.09.2020

1 Identification of the substance/mixture and of the company/undertaking

· Product identifier

· Trade name: Peak™ SE Primer (Part 1 of 2)

· Article number: 15076

· Index number: SDS 69-001.11

• Relevant identified uses of the substance or mixture and uses advised against Professional Dental Etchant

· Application of the substance / the mixture Professional Dental Etchant

· Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

Ultradent Products Inc.

505 W. Ultradent Drive (10200 S)

South Jordan, UT 84095-3942

USA

on line order support @ultradent.com

EC Responsible Person

Ultradent Products GmbH

Am Westhover Berg 30

51149 Cologne Germany

Email: infoDE@ultradent.com

Emergency Phone: +49(0)2203-35-92-0

· Further information obtainable from: Customer Service

· Emergency telephone number:

CHEMTREC (NORTH AMERICA) : (800) 424-9300 (INTERNATIONAL) : +(703) 527-3887

2 Hazards identification

- · Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



GHS05 corrosion

Skin Corr. 1A H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.



Skin Sens. 1 H317 May cause an allergic skin reaction.

- · Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The Regulation EC 1272/2008 on classification, labeling and packaging of substances and mixtures (CLP) shall not apply to a medical device in the finished state used in direct physical contact with the human body according to Art. 1.5 (d). Therefore, the product is exempted from the CLP labeling requirements, and no SDS is required by Regulation 1907/2006, Art. 2 (6c), REACH. Therefore, all given data, classification, and information on this SDS

(Contd. on page 2)

Printing date 19.10.2020 Revision: 18.09.2020

Trade name: Peak™ SE Primer (Part 1 of 2)

(Contd. of page 1)

are provided solely on a voluntary basis.

- · Hazard pictograms GHS02, GHS05, GHS07
- · Signal word Danger

· Hazard-determining components of labelling:

Trade Secret

2-Hydroxyethyl Methacrylate

Organophosphine Oxide

· Hazard statements

H226 Flammable liquid and vapour.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P233 Keep container tightly closed.
 P260 Do not breathe dusts or mists.
 P264 Wash thoroughly after handling.

P272 Contaminated work clothing should not be allowed out of the workplace.

P280 Wear protective gloves / eye protection / face protection. P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water

[or shower].

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P321 Specific treatment (see on this label).

P362+P364 Take off contaminated clothing and wash it before reuse.
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P363 Wash contaminated clothing before reuse.

P370+P378 In case of fire: Use for extinction: CO2, powder or water spray.

P403+P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

- · Other hazards
- · Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterisation: Mixtures
- · **Description:** Mixture of substances listed below with nonhazardous additions.

•	Dangerou	s com	ponents:
---	----------	-------	----------

(Contd. on page 3)

Printing date 19.10.2020 Revision: 18.09.2020

Trade name: Peak™ SE Primer (Part 1 of 2)

		(Contd. of page 2)
CAS: 868-77-9	2-Hydroxyethyl Methacrylate	>10-≤25%
EINECS: 212-782-2	♦ Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	
	Trade Secret	>2.5-≤10%
	♦ Skin Corr. 1A, H314; Eye Dam. 1, H318	
	Trade Secret	>2.5- ≤ 10%
	♦ Skin Corr. 1A, H314	
CAS: 162881-26-7	Organophosphine Oxide	≤2.5%
ELINCS: 423-340-5	♦ Skin Sens. 1, H317; Aquatic Chronic 4, H413	
· Additional informat	tion: For the wording of the listed hazard phrases refer to section 16.	

4 First aid measures

- Description of first aid measures
- General information: Immediately remove any clothing soiled by the product.
- · After inhalation: Seek medical treatment in case of complaints.
- · After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

· After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

After swallowing:

Do NOT induce vomiting.

Rinse mouth with water.

Drink plenty of water and provide fresh air. Call for a doctor immediately.

- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Firefighting measures

- Extinguishing media
- · Suitable extinguishing agents:

Carbon dioxide

Dry Chemical

Foam

· Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

· Advice for firefighters:

General: Evacuate all personnel; use protective equipment for fire-fighting. Use self-contained breathing apparatus when the product is involved in fire.

· Protective equipment:

Wear fully protective suit.

Mouth respiratory protective device.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

(Contd. on page 4)

Printing date 19.10.2020 Revision: 18.09.2020

Trade name: Peak™ SE Primer (Part 1 of 2)

(Contd. of page 3)

· Environmental precautions:

Dilute with plenty of water.

Do not allow to enter sewers/surface or ground water.

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Use neutralising agent.

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- · Handling:
- · Precautions for safe handling:

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.
- · Specific end use(s) Professiona Dental Etchant

8 Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

64-17-5 Ethyl Alcohol

WEL (Great Britain) Long-term value: 1920 mg/m³, 1000 ppm

- · Additional information: The lists valid during the making were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

(Contd. on page 5)

(Contd. of page 4)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 19.10.2020 Revision: 18.09.2020

Trade name: Peak™ SE Primer (Part 1 of 2)

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/the substance/the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact breakthrough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

· Body protection: Protective work clothing

9 Physical and chemical properties

· Information on basic physical and chemical properties

· General Information

· Appearance:

Form: Liquid
Colour: Yellow
Odour: Methacrylate
Odour threshold: Not determined.

• pH-value at 20 °C: 0.9-1.5-When mixed with part 2

· Change in condition

Melting point/freezing point: Undetermined.

Initial boiling point and boiling range: Undetermined.

· Flash point: <27 °C

· Flammability (solid, gas): Not applicable.

· **Decomposition temperature:** Not determined.

· Auto-ignition temperature: Product is not selfigniting.

• Explosive properties: Product is not explosive. However, formation of explosive air/vapour

mixtures are possible.

· Explosion limits:

Lower:Not determined.Upper:Not determined.

· Vapour pressure at 20 °C: 552 hPa

(Contd. on page 6)

Printing date 19.10.2020 Revision: 18.09.2020

Trade name: Peak™ SE Primer (Part 1 of 2)

		(Contd. of page 5
Density at 20 °C:	1.015 g/cm³	
Relative density	Not determined.	
· Vapour density	Not determined.	
· Evaporation rate	Not determined.	
· Solubility in / Miscibility with		
water:	Fully miscible.	
· Partition coefficient: n-octanol/water:	Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
· Solvent content:		
VOC (EC)	<65%	
Solids content:	<20.0 %	
· Other information	No further relevant information available.	

10 Stability and reactivity

- · Reactivity Polymerization occurs when exposed to visible light, ultraviolet light or extreme heat.
- · Chemical stability
- · Thermal decomposition / conditions to be avoided: Stable under recommended storage conditions
- · Possibility of hazardous reactions: No dangerous reactions known.
- · Conditions to avoid:

Direct Light

Heat

Flames

- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

64-17-5 E	Ethyl Alcohol		
Oral	LD50	5,600 mg/kg (Guinea pig)	
		3,400 mg/kg (mouse)	
		7,060 mg/kg (rat)	
	LC50 Fish	>10,000 mg/l (Fish)	
Inhalative	LC50/4 h	39 mg/l (mouse)	
		20,000 mg/l (rat)	
868-77-9	2-Hydroxyethyl M	ethacrylate	
Oral	LD50	3,275 mg/kg (mouse)	
		>5,000 mg/kg (rat)	
	LC50 Fish	>100 mg/l (Fish)	
Dermal	LD50	>3,000 mg/kg (rabbit)	

On page 7)

Printing date 19.10.2020 Revision: 18.09.2020

Trade name: Peak™ SE Primer (Part 1 of 2)

		(Contd. of page 6)	
LC50(Daphnia magna) 24.1 mg/l (daphnia)		24.1 mg/l (daphnia)	
162881-26	162881-26-7 Organophosphine Oxide		
Oral	LD50	>2,000 mg/kg (rat)	
	LC50 Fish	>0.09 mg/l (Fish) (Toxicity to fish)	
Dermal	LD50	>2,000 mg/kg (rat)	

- · Primary irritant effect:
- · Skin corrosion/irritation

Causes severe skin burns and eye damage.

· Serious eye damage/irritation

Causes serious eye damage.

· Respiratory or skin sensitisation

May cause an allergic skin reaction.

- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

12 Ecological information

· Toxicity

· Aquatic toxicity:		
64-17-5 Ethyl Alcohol		
Algae Toxicity	1,000 mg/l (Algae)	
868-77-9 2-Hydroxyethyl Methacrylate		
EC50	345 mg/l (Algae)	
162881-26-7 Organophosphine Oxide		
EC50 (static)	>1.175 mg/kg (daphnia) (Toxicity to aquatic invertebrates)	
Aqua toxicity	≥0.008 mg/l (daphnia) (Daphnia Magna Reproduction Test)	
Toxicity to Aquatic Plants (static)	>0.26 mg/l (Plant) (Toxicity to algae)	

- · Persistence and degradability No further relevant information available.
- · Behaviour in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system. Must not reach sewage water or drainage ditch undiluted or unneutralised.

Rinse off of bigger amounts into drains or the aquatic environment may lead to decreased pH-values. A low pH-value harms aquatic organisms. In the dilution of the use-level the pH-value is considerably increased, so that after the use of the product the aqueous waste, emptied into drains, is only low water-dangerous.

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

(Contd. on page 8)

Printing date 19.10.2020 Revision: 18.09.2020

Trade name: Peak™ SE Primer (Part 1 of 2)

· Other adverse effects No further relevant information available.

(Contd. of page 7)

13 Disposal considerations

- · Waste treatment methods
- · Recommendation Do not allow product to reach sewage system.

· Europ	· European waste catalogue		
HP3	Flammable		
HP8	Corrosive		
HP13	Sensitising		

· Uncleaned packaging:

14 Transport information

- Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agents: Water, if necessary together with cleansing agents.

1. 1. and post any of medical		
· UN-Number · ADR, IMDG, IATA	UN2920	
· UN proper shipping name · ADR	2920 CORROSIVE	

· ADR

2920 CORROSIVE LIQUID, FLAMMABLE, N.O.S.

(PHOSPHORUS PENTOXIDE, Ethyl Alcohol)

CORROSIVE LIQUID, FLAMMABLE, N.O.S.

(PHOSPHORUS PENTOXIDE, Ethyl Alcohol)

- · Transport hazard class(es)
- $\cdot ADR$



ClassLabel8 Corrosive substances.8+3

 \cdot *IMDG*



· Class 8 Corrosive substances. · Label 8/3

· IATA



· Class 8 Corrosive substances.

• *Label* 8 (3)

(Contd. on page 9)

Printing date 19.10.2020 Revision: 18.09.2020

Trade name: Peak™ SE Primer (Part 1 of 2)

	(Contd. of page
Packing group	
ADR, IMDG, IATA	II
Environmental hazards:	Not applicable.
Special precautions for user	Warning: Corrosive substances.
Hazard identification number (Kemler code):	83
EMS Number:	F-E,S-C
Segregation groups	Acids
Stowage Category	E
Stowage Code	SWI Protected from sources of heat.
	SW2 Clear of living quarters.
Tourse out in bull according to Assess II of Man	v 01
Transport in bulk according to Annex II of Mar and the IBC Code	
ana the IBC Code	Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	IL
Excepted quantities (EQ)	Code: E2
• •	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
Transport category	2
Tunnel restriction code	D/E
IMDG	
Limited quantities (LQ)	IL
Excepted quantities (EQ)	Code: E2
zacepica quantues (22)	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per unter packaging: 50 ml Maximum net quantity per outer packaging: 500 ml
	1 11 1 0 0
UN "Model Regulation":	UN 2920 CORROSIVE LIQUID, FLAMMABLE, N.O.
	(PHOSPHORUS PENTOXIDE, ETHYL ALCOHOL), 8 (3
	II

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment Annex II

None of the ingredients is listed.

· Chemical safety assessment:

Device is biocompatible when used as directed by dental professionals per ISO 10993-1

GB2

Printing date 19.10.2020 Revision: 18.09.2020

Trade name: Peak™ SE Primer (Part 1 of 2)

(Contd. of page 9)

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H225 Highly flammable liquid and vapour.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H413 May cause long lasting harmful effects to aquatic life.

- · Department issuing SDS: Environmental, Health & Safety
- · Contact: Customer Service
- · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2

Flam. Liq. 3: Flammable liquids – Category 3

Skin Corr. 1A: Skin corrosion/irritation – Category 1A

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

Aquatic Chronic 4: Hazardous to the aquatic environment - long-term aquatic hazard - Category 4

- GB2